

# Emulsol EKS-A

As practice shows, the most economical, reliable and convenient in manufacture of the reinforced concrete structures is the use of water emulsion lubricant **emulsol EKS-A**. Its high performance characteristics allow to:

- Remove the final product from the mold without any difficulties.
- Quickly and efficiently clean the molding containers.
- Apply **emulsol to lubricate the molds** with a layer of uniform thickness.

The Trading House “Promsmazki” offers to buy **emulsol EKS-A** at factory price, with minimal costs to search for products and place an order without having to worry about the timely delivery and profitability of the purchase.

We offer only high-quality products, delivered directly from the manufacturer in Russia and CIS countries.

The Trading House “Promsmazki” means profit, convenience and reliability.

Name of the indicators	Norm
1. Appearance	Liquid of brown up to dark brown color
2. Acid number, mg KOH/g	8,0-10,0
3. Stability of the emulsion: within 3 hours the oil is allocated at no more than %	0,8
4. Mass fraction of water, %, no more	0,2

Emulsol EKS-A is applied in the form of 20-30% of an emulsion.

Application in a condition of delivery is allowed.

Preparation of the working solution of an emulsol EKS-A is carried out by mixing of the concentrate with water solution of the calcinated soda at a temperature 60-70°C and hashing within 5-10 minutes before receiving a uniform emulsion.

Warranty period of storage 1 year.